

## VISTA-15P

### CONTROL PANEL



Honeywell's versatile VISTA-15P is the ideal choice for any residential installation. VISTA-15P gives you the ability to send alarm signals and upload/download via an Internet Protocol (IP), improving the speed at which information can be delivered to and from the control panel. In addition, when used with an AlarmNet Internet or digital communicator, the VISTA-15P can be installed in premises without TELCO lines – guaranteeing communication independent of any home infrastructure. Hardwired expansion, graphic keypad support, two-wire smoke detectors, scheduling options and a host of end-user and installer features separate the VISTA-15P from all other six-zone panels – offering you and your customers the most panel for the dollar.

## FEATURES

- IP alarm reporting and uploading/downloading capability for Internet and Intranet use via iGSMV, 7845i-ENT or GSMV
- Six on-board hardwired zones
  - 16 hardwired expansion zones totalling 22
  - 26 wireless expansion zones
- Supports two graphic touchscreen keypads
- Eight independent keyfob zones allow wireless keys to be programmed without using any of the 26 zones
- Eight output devices
  - Relays (Model 4204 Relay Modules, or 4229 Expansion Module), and/or
  - X-10® devices (when used with a 1361X10 Transformer)
- Two low current on-board trigger outputs
- 50 Event Log viewable at system keypads with time/date stamp
- 32 system user codes
- Two installer configurable zone types allows the installer to "create custom zone types" by assigning all zone attributes

- Multiple actions on output devices depending on system "state"
  - Turns light off when system arms
  - Turns same lights on when system disarms
  - Flashes same lights when system is in alarm
- Built-in phone line cut monitor with programmable delay and annunciation options
  - Display on system keypads
  - Trigger local sounders
  - Trigger system bell
- Supports four-wire and up to 16 two-wire smokes
  - Works with Sentrol CleanMe™ maintenance signal

### Valuable End-User Features

- Now viewable on system keypads:
  - Exit countdown
  - Time and date display\*
  - Event log\*
- Auto keypad backlighting on entry
- Keyswitch arming
- Programmable macro buttons and single-button arming
- A variety of wireless remote controls for single-button operation

- User Scheduling
  - Automatically activates X-10 and relays at programmed times
  - Latchkey reports to pagers
  - Auto arm/disarm
  - "User access" time windows
- Supports up to two numeric pagers
- VIP Module allows system control from any touchtone phone
- Chime by zone

### Security Dealer Features

- Automatic System Load Shed
  - During extended AC power fail, the system battery will be disconnected to prevent irreversible battery failure. Reduces service calls to replace batteries.
- Dynamic Signaling
  - Reduces redundant reporting to the central station when multiple reporting methods are used; i.e. digital dialer and AlarmNet Radio

\*Requires custom alpha keypad

# VISTA-15P

## CONTROL PANEL

### SPECIFICATIONS

---

#### Electrical

- Aux. power 12VDC, 600mA maximum
- Seven hour standby at 400mA aux. load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0 amps max.
- For UL installations, combined aux. and alarm output cannot exceed 700mA

#### Output Control

- Supports a maximum of eight output devices (combination of relays and/or X-10) plus two onboard triggers

#### Zones

- Six hardwired zones
- Selectable response 10msec, 350msec, 750msec
- 16 selectable zone types plus two configurable zone types
- Programmable swinger suppression

#### Expansion Devices

- 4219 – Eight hardwired zones – 16mA
- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)
- 4229 – Eight hardwired zones and two relays – 36mA (each active relay draws an additional 40mA)

#### Accessories

- iGSMV Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator
- GSMV Digital Cellular Communicator with Remote Service Capability
- 4286 VIP Voice Module – 220mA
- 5881ENL supports up to 8 zones – 60mA
- 5881ENM supports up to 16 zones – 60mA
- 5881ENH supports up to 32 zones – 50mA
- 5883 Transceiver supports up to 26 zones – 80mA

#### Keypads

- 6160 Custom Alpha (required for programming) – 100mA
- 6160V Custom Alpha Voice – 100mA
- 6150 Fixed English LCD – 85mA/40mA
- 6150V Fixed English Voice LCD – 85mA/40mA
- 6150RF Fixed English RF LCD – 85mA/40mA
- 6148 Fixed English LCD – 70mA/30mA
- 6270 Graphic Touchscreen
- 6272CBV Graphic Touchscreen with Voice (Black)
- 6272CSV Color Graphic Touchscreen with Voice (Silver)
- 6272CV Color Graphic Touchscreen with Voice (White)
- 8132 Advanced User Interface

#### Agency Listings

- ETL Residential Fire, Burglary and Commercial Burglary

#### Smoke Detectors

- Supports up to 16 two-wire smoke detectors
- Supports four-wire smoke detectors

#### Communications

- iGSMV Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator
- GSMV Digital Cellular Communicator with Remote Service Capability
- Touchtone or pulse
- Formats supported
  - ADEMCO Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - SESCOA/RADIONICS
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

## ORDERING

<b>VISTA-15P</b>	Control Panel
<b>VISTA-15PSIA</b>	Control Panel for CP-01 SIA certifications

#### For more information:

[www.honeywell.com/security/hsc](http://www.honeywell.com/security/hsc)

#### Automation and Control Solutions

Honeywell Security & Communications  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1.800.467.5875  
[www.honeywell.com](http://www.honeywell.com)

L/VISTA15PD/D  
June 2011  
© 2011 Honeywell International Inc.

# Honeywell